

# maximarine CYL SERIES

## Description

Maximarine CYL Series is a new generation cylinder lubricating oil that is produced with highly refined base oils and special additives, and meets the requirements of IMO 2020.

## Applications

It is used to lubricate the cylinders of new generation two-stroke marine engines operating under heavy mechanical load and thermal conditions, and using low or high sulfur fuel.

## Benefits

- It is designed for different needs and accommodates a wide range of applications.
- It keeps the wear on cylinders and liners under control.
- It prevents the formation of deposits and sediments in the pistons and rings.
- It provides a long service life at different ambient temperatures.

## Typical Specifications\*

		MAXIMARINE CYL 20	MAXIMARINE CYL 25	MAXIMARINE CYL 40	MAXIMARINE CYL 55	MAXIMARINE CYL 70	MAXIMARINE CYL 100
SAE Viscosity Grade		50	50	50	50	50	50
Density, 15 °C, kg/liter	ASTM D4052	0,900	0,900	0,934	0,927	0,935	0,952
Flash Point COC, °C	ASTM D92	270	270	270	270	270	270
Viscosity, 100 °C, mm <sup>2</sup> /s	ASTM D445	19	19	19	19	19	19
Viscosity Index	ASTM D2270	98	98	98	98	98	98
T.B.N., mgKOH/gr	ASTM D2896	20	25	40	55	70	100
Pour Point, °C	ASTM D97	-15	-15	-15	-15	-15	-15

\* Values shown may differ between productions.



**Petrol Ofisi**