



SAFETY DATA SHEET

MAXIMUS TURBO DIESEL S 15W-40

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name MAXIMUS TURBO DIESEL S 15W-40

Product number 11344

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Engine oil.

1.3. Details of the supplier of the safety data sheet

Supplier PETROL OFİSİ A.Ş.
 Ünalın Mahallesi, Libadiye Caddesi No: 82F Kat: 2-3-4, 34700 Üsküdar/ İstanbul
 Tel: +90 850 339 1919
 Fax: +90 216 275 3854
 madeniyag@petrolofisi.com.tr

1.4. Emergency telephone number

Emergency telephone Madeni Yağ Müşteri Hizmetleri: 0850 339 19 19 (mesai saatleri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

**Lubricating Oils, complex combination of hydrocarbons
 obtained from solvent extraction and dewaxing.(C15-C50)** **80-95%**

CAS number: 74869-22-0 EC number: 278-012-2

See Section 8 for occupational exposure limits.

Classification

Not Classified

MAXIMUS TURBO DIESEL S 15W-40

Zinc alkyldithiophosphate	<1%
CAS number: 68649-42-3	EC number: 272-028-3
Classification	
Skin Irrit. 2 - H315	
Eye Dam. 1 - H318	
Aquatic Chronic 2 - H411	
Calcium long chain alkylphenate sulfide	<1%
CAS number: —	
Classification	
Aquatic Chronic 4 - H413	
Calcium long chain alkaryl sulfonate	<1%
CAS number: —	
Classification	
Skin Irrit. 2 - H315	

The full text for all hazard statements is displayed in Section 16.

Composition comments Some substances are not classified by legislation. They are self classified by the manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Get medical attention if any discomfort continues.
Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation	No specific symptoms known.
Ingestion	No specific symptoms known.
Skin contact	No specific symptoms known.
Eye contact	No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific treatment. Treat symptomatically.

SECTION 5: Firefighting measures

MAXIMUS TURBO DIESEL S 15W-40

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with the following media: Foam, carbon dioxide or dry powder.

Unsuitable extinguishing media Do not use the following: Water.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during firefighting Avoid breathing fire gases or vapours. Control run-off water by containing and keeping it out of sewers and watercourses.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)

None of the components has assigned exposure limits.

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50) (CAS: 74869-22-0)

Ingredient comments There is no approximate limit value for this product. Steam, fog or smoke should be controlled to the lowest possible level.

MAXIMUS TURBO DIESEL S 15W-40

Biological limit values	No information available.
DNEL	No information available.
DMEL	No information available.
PNEC	No information available.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Nitrile rubber. Polyvinyl chloride (PVC).

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Brown.
Flash point	228°C OC (Open cup).
Relative density	0.88 g/ml @ 15°C
Viscosity	15-16.3 cSt @ 100°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

MAXIMUS TURBO DIESEL S 15W-40

Possibility of hazardous reactions Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidising agents.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed.

Skin contact Liquid may irritate skin.

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility The product is immiscible with water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The packaging must be empty (drop-free when inverted).

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Environmental Manager must be informed of all major spillages. Avoid the spillage or runoff entering drains, sewers or watercourses.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

MAXIMUS TURBO DIESEL S 15W-40

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
Guidance	Workplace Exposure Limits EH40. CHIP for everyone HSG228. Approved Classification and Labelling Guide (Sixth edition) L131. Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

SECTION 16: Other information

Key literature references and sources for data	This SDS is prepared based on the information received from raw material suppliers.
Revision comments	Revised classification.
Issued by	Emrah Parmak
Revision date	24/03/2016
Revision	2
Supersedes date	17/06/2011
Hazard statements in full	H315 Causes skin irritation. H318 Causes serious eye damage. H411 Toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.