



SAFETY DATA SHEET

KALIP YAGI M 20

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name KALIP YAGI M 20

Product number 29190

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial oil

1.3. Details of the supplier of the safety data sheet

Supplier PETROL OFİSİ A.Ş.
Ünalan Mahallesi, Libadiye Caddesi No: 82F Kat: 2-3-4, 34700 Üsküdar/ İstanbul
Tel: +90 850 339 1919
Fax: +90 216 275 3854
madeniyag@petrolofisi.com.tr

1.4. Emergency telephone number

Emergency telephone Madeni Yağ Müşteri Hizmetleri: 0850 339 19 19 (mesai saatleri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Asp. Tox. 1 - H304

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H304 May be fatal if swallowed and enters airways.

Precautionary statements P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
P405 Store locked up.
P501 Dispose of contents/ container in accordance with national regulations.

Contains Kerosine (Petroleum); Straight Run Kerosine

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

KALIP YAGI M 20

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)	80-95%
--	---------------

CAS number: 74869-22-0

EC number: 278-012-2

See Section 8 for occupational exposure limits.

Classification

Not Classified

KEROSINE (PETROLEUM); STRAIGHT RUN KEROSENE	20-25%
--	---------------

CAS number: 8008-20-6

EC number: 232-366-4

Classification

Asp. Tox. 1 - H304

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.
Ingestion	Rinse mouth thoroughly with water. Get medical attention if any discomfort continues. Do not induce vomiting.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
Eye contact	Remove affected person from source of contamination. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed**4.3. Indication of any immediate medical attention and special treatment needed**

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Dry chemicals. Do not use water, if avoidable. Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture**5.3. Advice for firefighters**

Protective actions during firefighting Avoid breathing fire gases or vapours. Ventilate closed spaces before entering them.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Contain spillage with sand, earth or other suitable non-combustible material. Spilled product makes the surface slippery. Product vapor may infiltrate the sewer network and may reach remote ignition sources since product vapor is heavier than air. In case of sea spills, water barriers should be used in order to prevent spill from spreading. Product on sea surface should be recovered.

KALIP YAGI M 20

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Avoid the spillage or runoff entering drains, sewers or watercourses. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation.
--------------------------------	---

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions	Avoid spilling. Avoid contact with skin and eyes. Do not eat, drink or smoke when using the product.
--------------------------	--

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container. Do not remove warning signs on tanks. Contaminated cloth, paper, etc. should be immediately discarded. Light hydrocarbons accumulate at upper levels of tank and constitutes a risk of combustion. Therefore, static electricity should be discharged. Precautions should be taken during loading and discharge.
----------------------------	---

Storage class	Chemical storage.
----------------------	-------------------

7.3. Specific end use(s)

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)

None of the components has assigned exposure limits.

Ingredient comments	WEL = Workplace Exposure Limits
----------------------------	---------------------------------

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50) (CAS: 74869-22-0)

Ingredient comments	There is no approximate limit value for this product. Steam, fog or smoke should be controlled to the lowest possible level.
Biological limit values	No information available.
DNEL	No information available.
DMEL	No information available.
PNEC	No information available.

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

KALIP YAGI M 20

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible.
Other skin and body protection	Wear appropriate clothing to prevent any possibility of skin contact.
Hygiene measures	Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.
Respiratory protection	No specific recommendations. Respiratory protection may be required if excessive airborne contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Yellow.
Flash point	119°C OC (Open cup).
Relative density	0.86 g/ml @ 15°C
Viscosity	16.8 cSt @ 40°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

10.4. Conditions to avoid

Conditions to avoid	Avoid contact with strong oxidising agents.
----------------------------	---

10.5. Incompatible materials

10.6. Hazardous decomposition products

Hazardous decomposition products	Fire creates: Carbon monoxide (CO). Carbon dioxide (CO ₂).
---	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Inhalation	Irritating to respiratory system.
Ingestion	Harmful: may cause lung damage if swallowed.
Skin contact	Irritating to skin.
Eye contact	Irritating to eyes.

SECTION 12: Ecological information

KALIP YAGI M 20

Ecotoxicity May be harmful to aquatic organisms. Spills form film layer on water surface and prevent oxygen transfer

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility Spilt product pollutes underground water. The product is immiscible with water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

KALIP YAGI M 20

Guidance

Workplace Exposure Limits EH40.
CHIP for everyone HSG228.
Safety Data Sheets for Substances and Preparations.
Approved Classification and Labelling Guide (Sixth edition) L131.

15.2. Chemical safety assessment**SECTION 16: Other information**

Key literature references and sources for data This SDS is prepared based on the information received from raw material suppliers.

Revision comments Revised classification.

Issued by Emrah Parmak

Revision date 30/08/2016

Revision 3

Supersedes date 17/06/2011

SDS number 10279

Hazard statements in full H304 May be fatal if swallowed and enters airways.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.