

SAFETY DATA SHEET ULTRA GRES CS-146

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name ULTRA GRES CS-146

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses All-purpose industrial and automotive grease.

1.3. Details of the supplier of the safety data sheet

Supplier PETROL OFISI A.Ş.

Ünalan Mahallesi, Libadiye Caddesi No: 82F Kat: 2-3-4, 34700 Üsküdar/ Istanbul

Tel: +90 850 339 1919 Fax: +90 216 275 3854 madeniyag@petrolofisi.com.tr

1.4. Emergency telephone number

Emergency telephone Madeni Yağ Müşteri Hizmetleri: 0850 339 19 19 (mesai saatleri)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318

Environmental hazards Not Classified

2.2. Label elements

Hazard pictograms



Signal word Danger

Hazard statements H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements P264 Wash contaminated skin thoroughly after handling.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a POISON CENTER/ doctor.
P321 Specific treatment (see medical advice on this label).
P332+P313 If skin irritation occurs: Get medical advice/ attention.
P362+P364 Take off contaminated clothing and wash it before reuse.

Revision date: 19/10/2016 Revision: 2 Supersedes date: 17/06/2011

ULTRA GRES CS-146

Contains

calcium dihydroxide, Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs., Zinc alkyldithiophosphate

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)

40-60%

CAS number: 74869-22-0 EC number: 278-012-2

See Section 8 for occupational exposure limits.

Classification

Not Classified

calcium dihydroxide 1-5%

CAS number: 1305-62-0 EC number: 215-137-3

Classification

Eye Dam. 1 - H318

Benzenesulfonic acid, 4-C10-13-sec-alkyl derivs.

1-5%

CAS number: 85536-14-7

Classification

Acute Tox. 4 - H302 Skin Corr. 1C - H314 Eye Dam. 1 - H318 Aquatic Chronic 3 - H412

ETHANOL 1-5%

CAS number: 64-17-5 EC number: 200-578-6

Classification

Flam. Liq. 2 - H225

Zinc alkyldithiophosphate 1-5%

CAS number: 68649-42-3 EC number: 272-028-3

Classification

Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

Composition comments Some substances are not classified by legistlation. They are self classified by the

manufacturer. The DMSO extract by IP 346 of the oil is less than 3%

SECTION 4: First aid measures

4.1. Description of first aid measures

Revision date: 19/10/2016 Revision: 2 Supersedes date: 17/06/2011

ULTRA GRES CS-146

General information Get medical attention if any discomfort continues.

Inhalation Move affected person to fresh air at once. Rinse nose and mouth with water. Get medical

attention if any discomfort continues.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse

mouth thoroughly with water. Get medical attention if any discomfort continues.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15

minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort

continues.

4.2. Most important symptoms and effects, both acute and delayed

Inhalation No specific symptoms known.

Ingestion No specific symptoms known.

Skin contact No specific symptoms known.

Eye contact No specific symptoms known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctorNo specific treatment. Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Extinguish with the following media: Foam, carbon dioxide or

dry powder.

Unsuitable extinguishing

media

Do not use the following: Water.

5.2. Special hazards arising from the substance or mixture

Specific hazards Protection against nuisance dust must be used when the airborne concentration exceeds 10

mg/m3. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during

Avoid breathing fire gases or vapours. Control run-off water by containing and keeping it out

of sewers and watercourses.

Special protective equipment

for firefighters

firefighting

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into

containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering

drains, sewers or watercourses.

ULTRA GRES CS-146

6.4. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-C50)

None of the components has assigned exposure limits.

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

Short-term exposure limit (15-minute): WEL

WEL = Workplace Exposure Limit.

Lubricating Oils, complex combination of hydrocarbons obtained from solvent extraction and dewaxing.(C15-

C50) (CAS: 74869-22-0)

Ingredient comments There is no approximate limit value for this product. Steam, fog or smoke should be

controlled to the lowest possible level.

Biological limit values No information available.

DNEL No information available.

DMEL No information available.

PNEC No information available.

8.2. Exposure controls

Protective equipment







Appropriate engineering

controls

Provide adequate ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. The following protection should be worn: Chemical splash goggles or

face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. Wear protective gloves made of the

following material: Nitrile rubber. Polyvinyl chloride (PVC).

Other skin and body

protection

Wear appropriate clothing to prevent any possibility of skin contact.

Revision date: 19/10/2016 Revision: 2 Supersedes date: 17/06/2011

ULTRA GRES CS-146

Hygiene measures Do not smoke in work area. Wash at the end of each work shift and before eating, smoking

> and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin.

When using do not eat, drink or smoke.

Respiratory protection No specific recommendations. Respiratory protection may be required if excessive airborne

contamination occurs.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Brown.

Appearance Liquid. Colour

Flash point 228°C OC (Open cup).

Relative density 0.88 g/ml @ 15°C

Viscosity 15-16.3 cSt @ 100°C

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Under normal conditions of storage and use, no hazardous reactions will occur.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time. Avoid contact with strong oxidising

agents.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

Fire creates: Carbon monoxide (CO). Carbon dioxide (CO2).

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

1,785,714.0 ATE oral (mg/kg)

Inhalation Gas or vapour in high concentrations may irritate the respiratory system. Symptoms following

overexposure may include the following: Coughing.

Ingestion May cause discomfort if swallowed.

Skin contact Liquid may irritate skin.

ULTRA GRES CS-146

Eye contact Vapour or spray in the eyes may cause irritation and smarting.

SECTION 12: Ecological information

Ecotoxicity Not regarded as dangerous for the environment.

12.1. Toxicity

12.2. Persistence and degradability

12.3. Bioaccumulative potential

12.4. Mobility in soil

Mobility The product is immiscible with water and will spread on the water surface.

12.5. Results of PBT and vPvB assessment

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information The packaging must be empty (drop-free when inverted).

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Environmental Manager must be informed of all major

spillages. Avoid the spillage or runoff entering drains, sewers or watercourses.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods

(IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

Transport labels

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. **Annex II of MARPOL 73/78**

and the IBC Code

ULTRA GRES CS-146

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

Guidance Workplace Exposure Limits EH40.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

SECTION 16: Other information

Key literature references and

ana mis

This SDS is prepared based on the information received from raw material suppliers.

Revision comments

sources for data

Revised classification.

Issued by

Emrah Parmak

Revision date

19/10/2016

Revision

2

Supersedes date

17/06/2011

SDS number

20257

Hazard statements in full

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.